

GPS Safety Summary

Substance Name:

bis(3,5,5-trimethylhexanoyl) peroxide

1. General Statement

The substance is primarily used as a radical initiator. The substance is used at the industrial stage and is not sold to general population.

2. Chemical Identity

Name: bis(3,5,5-trimethylhexanoyl) peroxide

Brand names: Luperox® 219EN grades, Luperox® 219M grades,

Luperox® 219D37,5

Chemical name (IUPAC): bis(2,4,4-trimethylpentyl)peroxyanhydride

CAS number(s): 3851-87-4 EC number: 223-356-0 Molecular formula: $C_{18}H_{34}O_4$

Structure:

3. Use and applications

The substance is primarily used as a radical initiator to induce polymerisation (free radical polymerisation process) for the manufacture of plastic (LDPE, low-density polyethylene).

4. Physical / Chemical properties

Organic peroxides are thermally unstable substances or mixtures, which can undergo exothermic self-accelerating decomposition.

Property	Value		
Physical state	Liquid at 20 °C and 1013 hPa		
Colour	Colourless		
Odour	Characteristic		
Molecular weight	314.46 g/mol		
Density	0.89 g/cm ³ at 20°C		
Vapour pressure	<0.01 Pa at 25°C		
Freezing point	<-75°C		

Boiling point	Not relevant, the substance decomposes before boiling
Flash point	61°C at 1013 hPa
Self-Accelerating Decomposition Temperature (SADT)	20°C
Explosive properties	Non-explosive
Water solubility	Not relevant, instable in water.
Octanol-water partition coefficient (LogKow)	7 at 25°C

5. Health Effects

The substance has a low toxicity, although irritant to skin.

Effect Assessment	Result			
Acute Toxicity Oral / inhalation / dermal	No acute toxic effects following oral / dermal exposures. No data available following acute inhalation exposure.			
Irritation / corrosion Skin / eye	Causes skin irritation. Slightly irritant to eyes.			
Sensitisation	Does not cause skin allergic reaction.			
Toxicity after repeated exposure Oral / inhalation / dermal	Does not cause significant target toxicity following oral exposure.			
Genotoxicity / Mutagenicity	The substance has no in vitro genotoxic potential.			
Carcinogenicity	No data available.			
Reproductive / Developmental Toxicity	No data available.			

6. Environmental Effects

When released in water, bis(3,5,5-trimethylhexanoyl) peroxide is quickly hydrolysed and is readily biodegradable. The substance has a low toxicity to aquatic life.

Effect Assessment	Result
Aquatic Toxicity	Harmful to algae and daphnids

Fate and behaviour	Result
Biodegradation	Readily biodegradable
Bioaccumulation potential	No potential to bioaccumulate
PBT / vPvB conclusion	Not considered as PBT nor vPvB

7. Exposure

7.1 Human health

The manufacture of organic peroxide is a closed process that occurs behind anti-deflagration walls, which minimizes worker exposure during the production process.

However, workers can be exposed during loading/unloading operations, mixing, sampling or maintenance operations.

The primary routes of industrial/professional exposure of the substance are skin contact and inhalation.

In addition, the general population is not expected to be exposed to this organic peroxide by inhalation, dermal or oral exposure, as the product does not remain in the plastic products.

Based on the risk assessment, risk is controlled when activities are carried out under conditions recommended in the extended safety data sheet (chapter 8 and exposure scenarios).

7.2 Environment

Releases of organic peroxides into the environment are to be expected during production, processing (formulation) and industrial uses mainly via wastewater and lesser amounts via emissions of vapour (due to its physical state and its vapour pressure).

Potential release during production is treated by on-site and off-site risk management measures.

The substance is used for production of polymers, which can either be dry or wet processes. In case of wet processes, releases to water have to be directed to wastewater treatment plant.

The substance is used in low quantity in polymer production, and is almost totally consumed during the process. Therefore the release to environment is very low. Furthermore, the substance is unstable in water and is rapidly degraded in product of low concern for environment. The use is considered as safe for the environment (this was confirmed by a quantitative risk assessment performed in the framework of REACH regulation).

8. Risk Management recommendations

Human health measures				
Eye/Face protection	Safety glasses/goggles. Half-mask during the discharge.			
Skin protection	Protective suit.			
Hand protection	Gloves: PVC, neoprene (suitable gloves tested to EN374).			
Respiratory protection	Suitable respiratory equipment in case of insufficient ventilation.			
Organizational measures	Ensure workers are duly trained to minimize exposure.			
Engineering control	Provide sufficient air exchange and/or exhaust ventilation in work rooms.			

Environmental measures

Can be discharged in waste water, when in compliance with local regulations. Do not spread sludge on natural soils.

Eliminate the product by incineration after dilution in a suitable flammable solvent (in accordance with local and national regulations) – amount of active oxygen must be below 1%.

Storage and handling

Strictly limit the quantities of product in the work area to those which are absolutely necessary for the work in hand. Great cleanliness in work areas is a necessary and important factor for safety. Never weigh out in the storage room. Handle and open container with care (risk of overpressurization in containers). Eliminate all sources of ignition, and do not generate flames or sparks. Take precautionary measures against static discharges.

Apply earthing when transferring from one container to another. Confinement must be avoided. Use explosion protected equipment.

Use non-sparking tools in areas where explosive vapor/air mixtures may occur. Keep product and emptied container away from heat and sources of ignition. Do not cut or weld on or near this container even when empty. Keep away from incompatible materials such as: strong oxidizing agents, powerful reducers, acids, bases, amines, transition metal salts, sulphur compounds, rust, ash, dusts (risk of self-accelerating exothermic decomposition) Never return any product to the container from which it was originally removed (risk of decomposition).

For the most concentrated products (75%): avoid temperatures above -5 °C (prevention of fire and explosion). Storage buildings must be built and equipped so as not to exceed the maximum proscribed temperature limit.

9. Regulatory Information / Classification and Labelling

9.1 Regulatory Information

This substance has been registered under:

EU Regulation EC 1907/2006 (REACH)

As organic peroxides are sensitive substances (as they are liable to exothermic decomposition), the carriage of tert-amyl hydroperoxide is strongly regulated, under the rules and conditions of class 5.2 of UN Recommendations on the Transport of Dangerous Goods regulation.

%	Form	UN Number	Classification	OP Category
>52- 82%	liquid	UN 3115	OP Type D, Liquid, temperature controlled	Type D: (i) detonates partially, does not deflagrate rapidly, no violent effects when heated under confinement; or (ii) does not detonate at all, deflagrates slowly, no violent effects when heated under confinement; or (iii) does not detonate or deflagrate, medium effect when heated under confinement.
≤52%	stable dispersi on in water	UN 3119	OP Type F, Liquid, temperature controlled	Type F: neither detonates in the cavitated state nor deflagrates at all and shows only a low or no effect when heated under confinement as well as low or no explosive power.
>38- 52%	liquid	UN 3119	OP Type F, Liquid, temperature controlled	Type F: neither detonates in the cavitated state nor deflagrates at all and shows only a low or no effect when heated under confinement as well as low or no explosive power
≤38%	liquid	UN 3119	OP Type F, Liquid, temperature controlled	Type F: neither detonates in the cavitated state nor deflagrates at all and shows only a low or no effect when heated under confinement as well as low or no explosive power.

9.2 Classification and labelling

Under GHS substances are classified according to their physical, health, and environmental hazards. The hazards are communicated via specific labels and the eSDS. GHS attempts to standardize hazard communication so that the intended audience (workers, consumers, transport workers, and emergency responders) can better understand the hazards of the chemicals in use. Substances registered for REACH are classified according CLP (EC) 1272/2008, implementation of the GHS in the European Union.

Classification

According to REGULATION (EC) no 1272/2008:

- Organic peroxide; type D; Heating may cause a fire.
- Skin irritation; Category 2; Causes skin irritation.
- Skin sensitisation; Category 1; May cause an allergic skin reaction.

Signal word

Danger

Pictogram

GHS02: Flame



GHS07: Exclamation mark



Hazard statement

- H242: Heating may cause a fire.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.

Alternative classification according to Globally Harmonized System (GHS)

Aquatic acute; Category 3; Harmful to aquatic life

10. Contact Information within Company

For further information on this substance or product safety summary in general, please contact:

- arkema.peroxides-reach-uses@arkema.com
- ICCA portal where the GPS Safety Summary is posted:
 http://www.icca-chem.org/en/Home/ICCA-initiatives/global-product-strategy/

11. Date of Issues / Revision

Date of issue: 2014/07/10

— Date of revision:

12. Disclaimer

The information contained in this paper is intended as advice only and whilst the information is provided in utmost good faith and has been based on the best information currently available, is to be relied upon at the user's own risk.

NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN.

No liability will be accepted by ARKEMA for damages of any nature whatsoever resulting from the use of or reliance on the information.