

FORANE[®]

REFRIGERANTS

CAS No. 75-10-5 (HFC-32) / 354-33-6 (HFC-125) / 420-46-2 (HFC-143a) / 811-97-2 (HFC-134a)

Forane[®] 427A

Difluoromethane (HFC-32) / Pentafluoroethane (HFC-125) / 1,1,1-Trifluoroethane (HFC-143a) / 1,1,1,2-Tetrafluoroethane (HFC-134a)

GENERAL DESCRIPTION

Forane[®] 427A is a blend of HFC components with zero ozone depletion potential. It is designed as an HFC refrigerant retrofit for R22 applications such as retail food refrigeration, industrial process air conditioning, chillers, household refrigerators and freezers, residential and light commercial air conditioning and heat pumps, and air conditioning for buses and passenger trains.

SPECIFICATIONS

(Meets AHRI 700 - 2017 Specifications)

	Maximum (unless otherwise indicated)	Tolerance
Difluoromethane (HFC-32), wt %	15.0 (nominal)	± 2.0 %
Pentafluoroethane (HFC-125), wt %	25.0 (nominal)	± 2.0 %
1,1,1-Trifluoroethane (HFC-143a), wt %	10.0 (nominal)	± 2.0 %
1,1,1,2-Tetrafluoroethane (HFC-134a), wt %	50.0 (nominal)	± 2.0 %
Air and Other Non-condensable Gases, vol %	1.5	
Volatile Impurities, wt %	0.5	
High Boiling Residue, vol %	0.01	
Moisture (H ₂ O), ppm by wt	10	
Acidity, ppm by wt (as HCl)	1.0	
Chloride, no visible turbidity (indicates about 3 ppm)	Pass	
Particulates, visually clean to pass	Pass	

PROPERTIES

Appearance	Colorless liquefied gas
Odor	Faint, ether-like odor
Molecular Mass (g/mole of blend)	90.4
Bubble Point at 1 atm	-45.4°F / -43.0°C
Dew Point at 1 atm	-33.3°F / -36.3°C
Flammable Limits (LFL, UFL), vol % (1 atm, 25°C)	NA / NA
ANSI/ASHRAE Standard 34 Safety Group Classification	A1
Ozone Depletion Potential (ODP) (CFC-11 = 1.0)	0
Global Warming Potential (GWP ⁽¹⁾) (CO ₂ = 1.0)	2,025

(1) GWP according to IPCC AR5. Values for 100-year time horizon

TEMPERATURE

	50°F	70°F	105°F	115°F	130°F
Vapor Pressure, psia ⁽²⁾	91.1	220.5	220.1	253.6	311.2
Liquid Density, lb./ft ³ (2)	74.3	71.5	65.9	54.1	61.1

(2) Generated using NIST REFPROP Version 10.0

Customer Service: (800) 245-5858

Technical Service Team: (800) 738-7695

forane.com

BEFORE HANDLING THIS MATERIAL, READ AND UNDERSTAND THE SDS (SAFETY DATA SHEET) FOR ADDITIONAL INFORMATION ON PERSONAL PROTECTIVE EQUIPMENT AND FOR SAFETY, HEALTH AND ENVIRONMENTAL INFORMATION.

Forane[®] is a registered trademark of Arkema.
UL[®] is a registered trademark of Underwriters Laboratories, Inc.



Headquarters: Arkema France

420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0) 1 49 00 80 80
F +33 (0) 1 49 00 83 96
arkema.com

Arkema Inc.

900 First Avenue
King of Prussia, PA 19406
T +1 610 205 7000
F +1 610 205 7497
arkema.com

Please consult Arkema's disclaimer regarding the use of Arkema's products on <http://www.arkema.com/usa/en/products/product-safety/disclaimer/index.html>
Arkema - a French "société anonyme", registered with the Commercial and Companies Register of Nanterre under number 319 632 790

© 2022 Arkema Inc. All rights reserved.

arkema.com

ARKEMA