

# TECHNICAL DATA SHEET

# **CRAYVALLAC® WN-1535**

Micronised modified polypropylene wax for waterborne systems

# **Micronised wax**

## **TYPICAL CHARACTERISTICS**

Nature Special wax

Appearance Off-white micronized powder

Active Content (%) 100

Particle size distribution DV. 5:4 - 7 µm / DV. 9:11 - 13 µm / Max. particle

size : 26 µm

Melting Point (°C) 150

#### **DESCRIPTION**

CRAYVALLAC® WN-1535 is a micronised modified polypropylene wax designed as a matting agent for use in inks and liquid coatings while providing a smooth and silky feel appearance. It is especially designed for water-based systems where it shows ease of dispersability.

#### **RECOMMENDED ADDITION LEVEL**

0.5 - 2.5% under low to medium shear dispersion

### **STANDARD PACKAGING**

Other packaging may be available upon request

• 15 Kg Bag

# **HANDLING & STORAGE**

It should be stored in the original containers in a dry place at temperatures between 5°C (41°F) and 30°C (86°F). Avoid exposure to direct sunlight or frost. In these conditions, this product should be used within 48 months from production.

## **PROCESSING INSTRUCTIONS**

CRAYVALLAC® WN-1535 is readily dispersed into coating formulations using a variety of techniques e.g. high-speed dispersers, bead mills and triple roll mills. In general, micronised waxes are best incorporated into coating systems at the first stage of formulation. Alternatively, waxes may be added to the formulation immediately following the dispersion stage but prior to the final letdown.

## **HEALTH AND ENVIRONMENTAL DATA**

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

#### **MARKETS**

#### **Coatings & Inks**

- Architectural Coating
- Graphic Arts
- Industrial Coating

#### **KEY BENEFITS**

#### **FORMULATION**

- · Ready to use
- Easy handling
- Post addition

#### FILM PROPERTIES

- Matting effect
- Transparency
- Stain resistance

#### SAFER SOLUTIONS

- APEO Free\*
- Heavy Metal Free\*
- Solvent Free\*
- \* Not intentionally added but not specifically measured (not part of product specification)

**Headquarter: Arkema France** 51, Esplanade du Général de Gaulle 92800 Puteaux – France T +33 (0)1 49 00 80 80

