

TECHNICAL DATA SHEET

CorinTH™ 6860

High molecular weight sulfonated polymer

Sulfonic copolymer

TYPICAL CHARACTERISTICS

| | |
|------------------------------|---|
| Nature | Acrylic sulfonic copolymer in water solution |
| Appearance | Semi-viscous yellow to amber liquid |
| Solid Content (%) | 37 |
| pH | 4.8 |
| Brookfield viscosity (mPa.s) | 310 |

DESCRIPTION

CorinTH™ 6860 is a high content sulfonate copolymer with anti-scaling and dispersing properties. CorinTH™ 6860 demonstrates good anti-scaling of CaCO₃ and silicates. It is an excellent dispersant of silt and a good phosphonate stabilizer.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC • 220L Plastic Drum

HANDLING & STORAGE

The product should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.
In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Water Management

- Water Treatment
 - Water Treatment

KEY BENEFITS

- Dispersion effect



Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA