

TECHNICAL DATA SHEET

CorinTH™ 805-S

Low molecular weight and neutralized scale inhibitor

Acrylic homopolymer

TYPICAL CHARACTERISTICS

Nature	Polyacrylic acid, sodium salt
Appearance	Slightly viscous liquid, colorless to pale yellow
Solid Content (%)	42
pH	8
Brookfield viscosity (mPa.s)	165
Specific gravity	1.31

DESCRIPTION

Excellent multi-purpose scale-inhibitor especially for scale of CaCO₃, CaSO₄, suitable for neutral and alkaline formulation.

STANDARD PACKAGING

Other packaging may be available upon request
• 1000L IBC • 220L Drum

HANDLING & STORAGE

The product should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.
In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Water Management

- Water Treatment
- Water Treatment

KEY BENEFITS

- Crystal distortion
- Threshold effect



Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA