

TECHNICAL DATA SHEET

RHEOSPERSE™ 4050 D

Dispersing agent specifically designed for calcium hydroxide slurries

TYPICAL CHARACTERISTICS

Nature	Polyether Polycarboxylate in aqueous solution
Appearance	Viscous liquid
Solid Content (%)	10
pH	3,3

DESCRIPTION

Rheospense™ 4050 D improves dispersion of Calcium Hydroxide in water at high concentrations. Rheospense™ 4050 D is not affected by high salt concentrations and can be used in a wide range of alkaline pH.

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC

HANDLING & STORAGE

RHEOSPERSE™ 4050 D should be protected from the effects of weathering and stored between 5 and 40°C. Once opened, packaging should be resealed immediately after use.
In these conditions, this product should be used within 12 months from delivery.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Mining & Metallurgy

- Minerals
 - Lime

KEY BENEFITS

- | | |
|------------------------|-----------------|
| • Downstream market | Water treatment |
| • Suspension stability | < 6 months |
| • Type of use | Dispersion |

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA