

TECHNICAL DATA SHEET

TOPSPERSE™ SFS

Surfactant Free Succinate for curtain coating

TYPICAL CHARACTERISTICS

| | |
|------------------------------|------------------------------|
| Nature | Non ionic surfactant |
| Appearance | Viscous liquid |
| pH | 6 |
| Brookfield viscosity (mPa.s) | < 100 mPas at 25°C |
| Specific gravity | 1.01 |

DESCRIPTION

Topsperser™ SFS is a surfactant free succinate have been developed to comply with more sustainable aspects. Topsperser™ SFS as Alcohol Ethoxylated surfactant allows a good efficiency at low and high flow rates. Topsperser™ SFS helps to control the curtain stability.

RECOMMENDED ADDITION LEVEL

0.05 to 0.5 as received

STANDARD PACKAGING

Other packaging may be available upon request

- 1000L IBC
- 220L Drum

HANDLING & STORAGE

Surfactant must be stored inside a building at a constant temperature between 5°C and 30°C. The shel life is 6 months in the unopened original packaging, stored in a cool and dry place, protected from heat and frost, without exposure to direct sunlight.

Natural processes might cause cloudiness or a sediment that disappear by homogenising the product without any loss of quality, e-g. by slight heating and stirring. If applicable, we strongly recommend to homogenise the product before use. During storage, a change of pH might be observed for this product, but this has no effect on its quality.

In these conditions, this product should be used within 6 months from delivery.

PROCESSING INSTRUCTIONS

Shall be introduced at the end of the coating color preparation after the pigments and the binders and prior to the pH adjustment with a diluted caustic soda.

HEALTH AND ENVIRONMENTAL DATA

For safe handling please refer to the Safety Data Sheet. For more information about health and environmental data, please contact us.

MARKETS

Pulp & Paper

- Board Coating
- Paper Coating

KEY BENEFITS

Headquarters: Arkema France
51, Esplanade du Général de Gaulle
92800 Puteaux – France
T +33 (0)1 49 00 80 80