

## RHEOLOGICAL ADDITIVE FOR HIGH TO MEDIUM POLARITY SYSTEMS

**Crayvallac® LA-150** is a liquid rheological additive. It has been designed for high to medium polarity formulations (for example xylene/ butanol).

- ✦ **Easy to use** due to liquid form and low viscosity
- ✦ **Post-addition** for final viscosity adjustment
- ✦ **NMP-free** and non labelled additive

Based on a modified urea chemistry **Crayvallac® LA-150** has been successfully designed for many systems with a **high to medium polarity range**.

**Crayvallac® LA-150** is mainly used in:

- ✦ Protective coatings
- ✦ General industry
- ✦ Coil coatings
- ✦ Industrial wood finishes

**Crayvallac® LA-150** develops a thixotropic behavior allowing perfect balance between film aspect and thickness control.

**Key benefits:**

**CRAYVALLAC**® LA-150  
BY ARKEMA

Easy  
incorporation  
Post  
addition

Anti-settling  
& stability

Film  
levelling

Sag  
resistance



# Rheology Modifier designed for Demanding High to Medium Polarity Systems

## Easy incorporation, post addition...



**Crayvallac® LA-150** can be **easily incorporated** in formulations by **post-addition** under low shear rates to ensure a **good homogeneity**

## ... Anti-settling

**Crayvallac® LA-150** provides **anti-settling** properties for enhanced **storage stability**



## Thixotropic behavior...



*Application of a 200 µm wet thickness*



**Crayvallac® LA-150** shows an **excellent thixotropy** with balanced **sag resistance** and **film levelling**

Contact us to discover all **our solutions** for **Coatings**