



Forane® 407A Refrigerant Basic Properties

Properties	Forane [®] 407A
*Average Molecular Weight (g/mol)	90.1
*Normal Boiling Point (NBP) (°F)	-49.0
*Latent Heat of Vaporization @ NBP (BTU/lb)	101.3
*Critical Temperature (°F)	180.1
*Critical Pressure (psia)	654.9
*Density of Saturated Vapor @ NBP (lb/ft³)	0.30
*Density of Saturated Liquid @ 77 °F (lb/ft³)	71.5
*Specific Heat of Saturated Vapor @ NPB (BTU/lb °F)	0.18
*Specific Heat of Saturated Liquid @ 77 °F (BTU/lb °F)	0.36
Ozone Depletion Potential (ODP) (CFC 11 = 1.0)	0
Global Warming Potential (GWP)	2,107
ASHRAE Safety Group Classification	A1
Occupational Exposure Limits (8 hr. time/wt. Avg.) (ppm)	1,000

*This data was generated using the NIST REFPROP Database

(Lemmon, E.W., Huber, M.L., McLinden, M.O. NIST Standard Reference Database 23: Reference Fluid Thermodynamic and Transport Properties-REFPROP, Version 9.0, National Institute of Standards and Technology, Standard Reference Data Program, Gaithersburg, 2010)

The information contained in this document is based on trials carried out by Arkema Research Centers and data selected from literature, but shall in no event be held to constitute or imply any warranty, undertaking, express or implied commitment from our part. Our formal specifications define the limit of our commitment. No liability whatsoever can be accepted by Arkema with regard to the handling, processing or use of the product or products concerned which must in all cases be employed in accordance with all relevant laws and/or regulations in force in the country or countries concerned.

The statements, technical information and recommendations contained herein are believed to be accurate as of the date hereof. Since the conditions and methods of use of the product and of the information referred to herein are beyond our control, Arkema expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information; NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE CONCERNING THE GOODS DESCRIBED OR THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be applicable when such product is used in combination with other materials or in any process. The user should thoroughly test any application before commercialization. Nothing contained herein constitutes a license to practice under any patent and it should not be construed as an inducement to infringe any patent and the user is advised to take appropriate steps to be sure that any proposed use of the product will not result in patent infringement.