



RHEOSOLVE™ T 633

Acrylic thickener for home care formulations

RHEOSOLVE™ T 633 is an acrylic thickener in aqueous dispersion specifically designed for the household, industrial and institutional detergent industry.

RHEOSOLVE™ T 633 is easy to use and provides instantaneous thickening effect.

• TYPICAL ANALYSIS

Nature: Acrylic copolymer in aqueous dispersion

Appearance (20°C): Low viscous white milky liquid

Solids content (%): 30

pH (20°C): 4

Specific gravity (20°C): 1.06

• ADVANTAGES

Highly Versatile Thickener at high pH

RHEOSOLVE™ T 633 allows an accurate adjustment of the rheology solving then many formulation issues even in very alkaline media.

Contribute to the granting of Ecolabels

RHEOSOLVE™ T 633 is non hazardous and also exempt from REACH.

• APPLICATIONS

Highly alkaline formulations

RHEOSOLVE™ T 633 can be used to efficiently thicken highly alkaline formulations (such as sodium or potassium hydroxide).

Formulations are available in our “Rheosolve T 6xx’ formulations book”

• STORAGE

RHEOSOLVE™ T 633 can be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure.

Once opened, packaging should be resealed immediately after use. In these conditions, products should be used within 12 months following the date of manufacture.

• STANDARD PACKAGING

- 1 000 l containers
- Bulk

• HEALTH & ENVIRONMENTAL DATA

Please refer to the Safety Data Sheet.

For information about ecolabels, please contact Coatex.

Website: www.coatex.com

Disclaimer: Please consult Arkema's disclaimer regarding the use of our products on <http://www.arkema.com/en/products/product-safety/disclaimer/> (2019/10/18)