



RHEOSOLVE™ T 650

Acrylic thickener for home care formulations

• TYPICAL ANALYSIS

Nature: Acrylic copolymer in aqueous dispersion

Appearance (20°C): Liquid

Solids content (%): 30

pH (20°C): 3

Specific gravity (20°C): 1.06

Compatibility: Soluble at pH > 7

• STORAGE

RHEOSOLVE™ T 650 will be irreversibly altered by frost. It should be protected from the effects of weathering and stored between 5 and 40°C and protected from direct sun exposure.

Once opened, packaging should be resealed immediately after use.

In these conditions, products should be used within 6 months after delivery.

• STANDARD PACKAGING

- 1 000 l containers
- Bulk

• HEALTH & ENVIRONMENTAL DATA

Please refer to the Material Safety Data Sheet.

Website: www.coatex.com

The information contained in this technical documentation relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. The information provided herein is based on technical data that Coatex believes to be reliable, provided that Coatex makes no representation or warranty as to the completeness or accuracy thereof and Coatex assumes no liability resulting from its use for any claims, losses, or damages of any third party. Recipients receiving this information must exercise their own judgement as to the appropriateness of its use and it is the user's responsibility to assess the material's suitability (including safety) for a particular purpose prior to such use. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used (2015/08/27)